

Make your winter ice and snow problems disappear

with a

WINTER WIZARD



- Front mounted with a front spread pattern gives weight to the driven wheels, whilst the grit has already started to work on the snow and adds traction.
- Industry proven hydraulically driven 'Pozi-Feed' stainless steel double auger system will spread all types of salt and grit wet or dry – brown or white
- Basic no-nonsense controls make the machine easy to operate and require minimal operator training

Watch the video online at www.thewinterwizard.com

The Winter Wizard – a hydraulically driven salt spreader/gritter for use with forklift trucks. The winter wizard has conveniently placed fork pockets which allow attachment to the front end of a forklift truck or fork lift tines in a safe and effective manner. It is hydraulically driven from the forklift truck's third service valve or side shift valve. Fitted with the Vale 'POZI-FEED' auger system which can spread all types of salt, wet or dry, brown or white. With a 0.20m³ hopper capacity to take approximately 250kg of salt.



- 0.20m³ Mild Steel Hopper
- Hydraulically driven stainless steel disc, with adjustable spread width from 1.3m to 9m (dependant on the material being spread)
- Manually adjustable spread width valve
- 100mm Stainless Steel 'Pozi – Feed' double augers providing positive salt feed even with wet material, driven hydraulically through a heavy duty high load hydraulic motor
- Pozi-Feed Augers run in maintenance free nylon bushes
- Manually adjustable application rate valve
- Hydraulically powered from the forklift truck's hydraulic circuit (3rd service or by piping into the side shift valves)
- Spreading action controlled by activation and de-activation of the forklift truck service valves
- Fork pockets with heel pins for safe mounting of the winter wizard
- Flat mesh top, complete with access hatch
- Metal work blast cleaned, prior to zinc rich powder prime and finished in polyester powder coat finish where possible
- Stainless steel fasteners used where possible
- Fluorescent markings on the side and front mounted black chevrons
- Overall dimensions length 1270mm, width 890mm, height 810mm



VALE ENGINEERING (YORK) LIMITED

Moor Farm, Moor Monkton, York, United Kingdom

Tel +44 (0) 1904 738533 • Fax +44 (0) 1904 737111

info@valeuk.com • www.valeuk.com